

Screen Diagonal Dimension	22 Inch	24 Inch	27 Inch	32 Inch
Viewable Area W*H(mm)	478.65(H)*260.28(V)	527.04(H)*296.46(V)	597.888(H)*336.312(V)	698.4(H)*392.85 (V)
LED Type	LED	LED	LED	LED
Screen Maximum Resolution	1920*1080	1920*1080	1920*1080	1920*1080
Supported Input Resolutions	720*400; 640*480; 800*600; 1024*768; 1280*1024; 1600*900;1920*1080	720*400; 640*480; 800*600; 1024*768; 1280*1024; 1600*900; 1920*1080	720*400; 640*480; 800*600; 1024*768; 1280*1024; 1600*900;1920*1080	720*400; 640*480; 800*600; 1024*768; 1280*1024; 1600*900;1920*1080
Refresh Rate	60 to 75Hz	60 to 75Hz	60 to 75Hz	60 to 75Hz
Color Depth	8 bits;16.7 million colors	8 bits;16.7 million colors	8 bits;16.7 million colors	8 bits;16.7 million colors
Brightness	250cd/m ²	250cd/m ²	250cd/m ²	300cd/m ²
Auto Adjust	Yes	Yes	Yes	Yes
Monitor Aspect Ratio	16:9	16:9	16:9	16:9
Display Aspect Ratio	OSD selectable16:9 or 4:3	OSD selectable16:9 or 4:3	OSD selectable16:9 or 4:3	OSD selectable16:9 or 4:3
Horizontal TV Lines	1080	1080	1080	1080
Contrast Ratio	3000:1	3000:1	3000:1	3000:1
Response Time (MS)	6.5	6.5	8	8
View Angle HN(Degrees)	178°/178°	178°/178°	178°/ 178°	178°/178°
Digital Video Inputs	HDMI up to 1920*1080	HDMI up to 1920*1080	HDMI up to 1920*1080	HDMI up to 1920*1080
Port Inputs	HDMI+VGA+AUDIO	HDMI+VGA+AUDIO	HDMI+VGA+AUDIO	HDMI+VGA+AUDIO
Port Outputs	NO	NO	NO	NO
Speakers	80Ω 1Watt/channel	80Ω 1Watt/channel	80Ω 1Watt/channel	80Ω 1Watt/channel
OSD Languages	English, Spanish, German, Chinese, French, Italian	English, Spanish, German, Chinese, French, Italian	English, Spanish, German, Chinese, French, Italian	English, Spanish, German, Chinese, French, Italian
Monitor Body Dimensions W*L*D(mm)	492.7*379.4*39.5	539.2*416.1*39.1	614.1*458.4*45.1	715.1*422.8*47.3
Packing Size (mm)	598*99*366	612*101*405	694*114*458	796*116*515
Case & Stand Material	Plastic	Plastic	Plastic	Plastic
VESA Mounting Pattern(mm)	75*75	75*75	75*75	75*75
Base/stand Included	Yes	Yes	Yes	Yes
Net Weight	2.0KG	2.74KG	3.84KG	5.65KG
Gross Weight	3.26KG	4.0KG	5.85KG	7.27KG
Power input	DC 12V/2A	DC 12V/2.5A	DC 12V/3A	DC 12V/4A
Power-Watts (On and	≤22W/≤0.5W	≤25W/≤0.5W	≤36W/≤0.5W	≤48W/≤0.5W
Operating Temperature	32°~104° (0°C~40°C)	32°~104° (0°C~40°C)	32°~104° (0°C~40°C)	32°~104° (0°C~40°C)
Storage Temperature	-4°~ 140° (-20°C ~ 60°C)	-4°~ 140° (-20°C ~ 60°C)	-4°~ 140° (-20°C ~ 60°C)	-4°~ 140° (-20°C ~ 60°C)
Operating Humidity	10 ~ 85%	10 ~ 85%	10 ~ 85%	10 ~ 85%
Accessory	Power Adapter, HDMI cable, User Manual	Power Adapter, HDMI cable, User Manual	Power Adapter, HDMI cable, User Manual	Power Adapter, HDMI cable, User Manual
Certifications	CE, FCC certificates	CE, FCC certificates	CE, FCC certificates	CE, FCC certificates

