

Screen Diagonal Dimension	43 / 49 / 55 / 65 Inch
Brightness	320cd/m <sup>2</sup>
LED Type	LED
Aspect Ratio	16:9
Resolution	1920*1080
Response Time	8ms
Contrast Ratio	1200:1
View Angle H/V(degrees)	178°/178°
Color Depth	16.7 million Colors
Refresh Rate	60Hz
Touch	10 Points
Touch Type	Infrared
Accuracy Touch	±2mm
Light Transmittance	Greater Than 86%
Response Time (MS)	≤8ms
Touch Interface	USB
CPU	Quad-core Cortex-a55 Up To 2.0ghz Mali-g52 GPU
RAM	2G
Flash	16G
Chipset	Rk3568
OS	Android 11.0
Input Interface	USB3.0*2, TF*1, Update Key*1
Output Interface	HDMI Out*1, Earphone*1
Communication Interface	RJ45
Video Format	H264, VP9, RV, WMV, AVS, H.265, MPEG4
Audio Format	MP3, WMA, WAV, APE, FLAG, MC, OGG, M4A, 3GPP Format
Image Format	JPG, BMP, PNG
Build-in Speakers	80 5Watt/channel
Lan	10m/100m Self-adaption
Wi-Fi	Supports The Wi-Fi 802.11b/g/n Protocol
Bluetooth	Bluetooth 4.0
Housing Material	Black Hardware+Black Profile+Black Screen Toughened Glass
Operation Time	7*16H
MTBF	30000H
Operation Temperature	0-40°C
Operation Humidity	10%-85% non-condensing
Storage Temperature	-20 ~ 60°C

- ❖ Panel is protected by high-grade tempered glass
- ❖ Android or X86 operation
- ❖ Digital signage content publishing system (optional)
- ❖ Integrated USB/Ethernet/WI-FI for signage updates
- ❖ Supports 10-point capacitance and IR touch control

